



PROMOTECNICA RC SRLS

CONSULENZA & PROMOZIONE MATERIALI PER "CICLO INTEGRATO DELL'ACQUA & INDUSTRIA"

Valori delle schedule secondo le norme ASME B36.10 e ASME B36.19

DN	Diametro	True	Schedula 10S	True	Schedula	True	Schedula
	(inch)	schedule 10	10S	schedule 40	40S (STD)	schedule 80	80S (XS)
8	1/4"	1,65	1,65	2,24	2,24	3,02	3,02
10	3/8"	1,65	1,65	2,31	2,31	3,20	3,20
15	1/2"	2,11	2,11	2,77	2,77	3,73	3,73
20	3/4"	2,11	2,11	2,87	2,87	3,91	3,91
25	1"	2,77	2,77	3,38	3,38	4,55	4,55
32	1 1/4"	2,77	2,77	3,56	3,56	4,85	4,85
40	1 1/2"	2,77	2,77	3,68	3,68	5,08	5,08
50	2"	2,77	2,77	3,91	3,91	5,54	5,54
65	2 1/2"	3,05	3,05	5,16	5,16	7,01	7,01
80	3"	3,05	3,05	5,49	5,49	7,62	7,62
100	4"	3,05	3,05	6,02	6,02	8,56	8,56
125	5"	3,40	3,40	6,55	6,55	9,53	9,53
150	6"	3,40	3,40	7,11	7,11	10,97	10,97
200	8"	3,76	3,76	8,18	8,18	12,70	12,70
250	10"	4,19	4,19	9,27	9,27	15,09	12,70
300	12"	4,57	4,57	10,31	9,52	17,48	12,70
350	14"	6,35	4,78	11,13	9,52	19,05	12,70
400	16"	6,35	4,78	12,70	9,52	21,44	12,70
450	18"	6,35	4,78	14,27	9,52	23,83	12,70
500	20"	6,35	5,54	15,09	9,52	26,19	12,70
600	24"	6,35	6,35	17,48	9,52	28,58	12,70